



## CF60 60 liter



Model:CF60

Description:

- \* 60L DC compressor fridge/freezer
- \* Capacity:60L
- \* Approval:CE,RoHS,SAA
- \* Temperature range: -18 °C ~+10°C
- \* Cooling Performance:UP to -18°C(at 32°C ambient temperature) Up to -13°C(at 43°C ambient temperature)
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Current:4.5A ON 12V
- \* Power consumption:54W
- \* Cooling unit:DC12/24v compressor
- \* Refrigerant:R134a
- \* Insulation:50 mmPolyurethane Foaming
- \* Accessories:DC cable, Recoverable basket, Instruction Manual, AC/DC adaptor(optional)
- \* excellent cooling performance and energy saving
- \* low noise, anti-vibration design
- \* digital display, temperature set and control
- \* stainless steel latches
- \* pre-coated metal body shell

[www.frinko.mk](http://www.frinko.mk) [www.klimafilija.mk](http://www.klimafilija.mk) +389 47 203 900



- \* automatic cut off at 10.8V
- \* Dual compartment ( big freezer small fridge room)

Packing & Loading:

- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:25KGS G.W.:27KGS
- \* Product size: 690\*490\*530mm
- \* EC Dimension: 730\*530\*590mm
- \* 1\*20"GP: 128pcs
- 1\*40"GP: 280pcs
- 1\*40"HQ: 280pcs



## CF80 80 liter



Model:CF80

Description:

- \* 80L DC compressor fridge/freezer
- \* Capacity:80L
- \* Approval:CE,RoHS,SAA
- \* Temperature range: -18 °C ~+10°C
- \* Cooling Performance:UP to -18°C(at 32°C ambient temperature) Up to -13°C(at 43°C ambient temperature)
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Current:5A ON 12V
- \* Power consumption:60W
- \* Cooling unit:DC12/24v compressor
- \* Refrigerant:R134a
- \* Insulation:50 mmPolyurethane Foaming
- \* Accessories:DC cable, Recoverable basket, Instruction Manual, AC/DC adaptor(optional)
- \* excellent cooling performance and energy saving
- \* low noise, anti-vibration design
- \* digital display, temperature set and control
- \* stainless steel latches
- \* pre-coated metal body shell

[www.frinko.mk](http://www.frinko.mk) [www.klimafilija.mk](http://www.klimafilija.mk) +389 47 203 900



- \* automatic cut off at 11V
- \* Dual compartment ( big freezer small fridge room)

Packing & Loading:

- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:27KGS G.W.:30KGS
- \* Product size: 690\*490\*620mm
- \* EC Dimension: 730\*530\*660mm
- \* 1\*20"GP: 102pcs
- 1\*40"GP: 210pcs
- 1\*40"HQ: 280pcs



## CF55 55 liter



Model:CF55

Description:

- \* 55L DC compressor fridge/freezer
- \* Capacity:55L
- \* Approval:CE,RoHS,SAA
- \* Temperature range: -18 °C ~+10°C
- \* Cooling Performance:UP to -18°C(at 32°C ambient temperature) Up to -13°C(at 43°C ambient temperature)
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Current:4.5A ON 12V
- \* Power consumption:54W
- \* Cooling unit:DC12/24v compressor
- \* Refrigerant:R134a
- \* Insulation:50 mmPolyurethane Foaming
- \* Accessories:DC cable, Recoverable basket, Instruction Manual, AC/DC adaptor(optional)
- \* excellent cooling performance and energy saving
- \* low noise, anti-vibration design
- \* digital display, temperature set and control
- \* stainless steel latches
- \* pre-coated metal body shell

[www.frinko.mk](http://www.frinko.mk) [www.klimafilia.mk](http://www.klimafilia.mk) +389 47 203 900



- \* automatic cut off at 10.8V
- \* Dual compartment ( big freezer small fridge room)

Packing & Loading:

- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:25KGS G.W.:27KGS
- \* Product size: 690\*490\*530mmm
- \* EC Dimension: 730\*530\*590mm
- \* 1\*20"GP: 128pcs
- 1\*40"GP: 280pcs
- 1\*40"HQ: 280pcs



## CF45 45 liter



Model:CF45

Description:

- \* 45L DC compressor fridge/freezer
- \* Capacity:45L
- \* Approval:CE,RoHS,SAA
- \* Temperature range: -18°C~+20°C,cooling to -18°C at 32°C ambient
- \* Cooling Performance:UP to -18°C(at 32°C ambient temperature) Up to -13°C(at 43°C ambient temperature)
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Current:4A ON 12V
- \* Power consumption:48W
- \* Cooling unit:DC12/24v compressor
- \* Refrigerant:R134a
- \* Insulation:60 mmPolyurethane Foaming
- \* Accessories:instruction manual, inside cabinet basket, DC cable, AC/DC adaptor(optional)
- \* LED display,temperature set and control
- \* automatic cut off at 9.5V
- \* stainless steel latches
- \* pre-coated metal body shell

Packing & Loading:

[www.frinko.mk](http://www.frinko.mk) [www.klimafilia.mk](http://www.klimafilia.mk) +389 47 203 900



- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:23KGS G.W.:25KGS
- \* Product size: 690x490x475mm
- \* EC Dimension: 730x530x530mmm
- \* 1\*20"GP: 136pcs
- 1\*40"GP: 280pcs
- 1\*40"HQ: 350pcs



## CF40 40 liter



Model:CF40

Description:

- \* 40L DC compressor fridge/freezer
- \* Capacity:40L
- \* Approval:CE,RoHS,SAA
- \* Temperature range: -18°C~+20°C,cooling to -18°C at 32°C ambient
- \* Cooling Performance:UP to -18°C(at 32°C ambient temperature) Up to -13°C(at 43°C ambient temperature)
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Current:4A ON 12V
- \* Power consumption:48W
- \* Cooling unit:DC12/24v compressor
- \* Refrigerant:R134a
- \* Insulation:50 mmPolyurethane Foaming
- \* Accessories:instruction manual, inside cabinet basket, DC cable, AC/DC adaptor(optional)
- \* LED display,temperature set and control
- \* automatic cut off at 10.8V
- \* stainless steel latches
- \* pre-coated metal body shell

Packing & Loading:

[www.frinko.mk](http://www.frinko.mk) [www.klimafilija.mk](http://www.klimafilija.mk) +389 47 203 900



- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:23KGS G.W.:25KGS
- \* Product size: 690x490x450mm
- \* EC Dimension: 730x530x500mm
- \* 1\*20"GP: 136pcs
- 1\*40"GP: 280pcs
- 1\*40"HQ: 350pcs



## CF35 35 liter



Model:CF35

Description:

- \* 35L DC compressor fridge/freezer
- \* Capacity:35L
- \* Approval:CE,RoHS,SAA
- \* Temperature range: -18°C~+10°C
- \* Cooling Performance:UP to -18°C(at 32°C ambient temperature) Up to -13°C(at 43°C ambient temperature)
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Current:3.5A ON 12V
- \* Power consumption:40W
- \* Cooling unit:DC12/24v compressor
- \* Refrigerant:R134a
- \* Insulation:40mm Polyurethane Foaming
- \* Accessories:DC cable, Recoverable basket, Instruction Manual, AC/DC adaptor(optional)
- \* excellent cooling performance and energy saving
- \* low noise, anti-vibration design
- \* digital display, temperature set and control
- \* stainless steel latches
- \* pre-coated metal body shell

[www.frinko.mk](http://www.frinko.mk) [www.klimafilia.mk](http://www.klimafilia.mk) +389 47 203 900



\* automatic cut off at 11V

#### Packing & Loading:

- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:18KGS G.W.:20KGS
- \* Product size: 562\*370\*540mm
- \* EC Dimension: 615\*430\*590mm
- \* 1\*20"GP: 204pcs
- 1\*40"GP: 408pcs
- 1\*40"HQ: 416pcs



## CF28 28 liter



Model:CF28

Description:

- \* 28L DC compressor fridge/freezer
- \* Capacity:28L
- \* Approval:CE,RoHS,SAA
- \* Temperature range: -18°C~+10°C
- \* Cooling Performance:UP to -18°C(at 32°C ambient temperature) Up to -13°C(at 43°C ambient temperature)
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Currency:3A ON 12V
- \* Power consumption:36W
- \* Cooling unit:DC12/24v compressor
- \* Refrigerant:R134a
- \* Insulation:40mm Polyurethane Foaming
- \* Accessories:DC cable, Recoverable basket, Instruction Manual, AC/DC adaptor(optional)
- \* excellent cooling performance and energy saving
- \* low noise, anti-vibration design
- \* digital display, temperature set and control
- \* stainless steel latches
- \* pre-coated metal body shell

[www.frinko.mk](http://www.frinko.mk) [www.klimafilia.mk](http://www.klimafilia.mk) +389 47 203 900



\* automatic cut off at 10.8V

Packing & Loading:

- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:16KGS G.W.:18KGS
- \* Product size: 562\*370\*430mm
- \* EC Dimension: 615\*430\*480mm
- \* 1\*20"GP: 248pcs
- 1\*40"GP: 496pcs
- 1\*40"HQ: 518pcs